



Product Service

Attestation of Conformity

No. N8A 16 09 76043 059

Holder of Certificate: Hengdian Group DMEGC Magnetics CO., LTDHengdian Industrial Zone,
322118 Dongyang, Zhejiang
PEOPLE'S REPUBLIC OF CHINA**Product:**Crystalline Silicon Terrestrial Photovoltaic (PV) Modules
Poly-Crystalline Silicon Photovoltaic Module

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for testing and certification. See also notes overleaf.

Test report no.: 704061088402-11**Date,** 2016-09-20

(Zhulin Zhang)



After preparation of the necessary technical documentation as well as the EU conformity declaration the required CE marking can be affixed on the product. That declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.

Page 1 of 4



Product Service

Attestation of Conformity

No. N8A 16 09 76043 059

Model(s):

DMxxx-P156-72 (xxx=245 to 350 in step of 5)
 DMxxx-P156-72BK (xxx=245 to 315 in step of 5)
 DMxxx-P156-60 (xxx=210 to 290 in step of 5)
 DMxxx-P156-60BK (xxx=210 to 260 in step of 5)
 DMxxx-P156-60L (xxx=210 to 290 in step of 5)
 DMxxx-P156-60BL (xxx=210 to 260 in step of 5)
 DMxxx-P156-48 (xxx=165 to 230 in step of 5)
 DMxxx-P156-48BK (xxx=165 to 210 in step of 5)
 DMxxx-P156-48L (xxx=165 to 230 in step of 5)
 DMxxx-P156-48BL (xxx=165 to 210 in step of 5)
 DMxxx-P156-36 (xxx=125 to 175 in step of 5)
 DMxxx-P156-36BK (xxx=125 to 155 in step of 5)
 DMxxx-P156-24 (xxx=85 to 115 in step of 5)
 DMxxx-P156-24BK (xxx=85 to 105 in step of 5)
 DMxxx-P156-60T (xxx=250 to 290 in step of 5)
 DMxxx-P156-72S (xxx=245 to 350 in step of 5)
 DMxxx-P156-72BKS (xxx=245 to 315 in step of 5)
 DMxxx-P156-60S (xxx=210 to 290 in step of 5)
 DMxxx-P156-60BKS (xxx=210 to 260 in step of 5)
 DMxxx-P156-60LS (xxx=210 to 290 in step of 5)
 DMxxx-P156-60BLS (xxx=210 to 260 in step of 5)
 DMxxx-P156-48S (xxx=165 to 230 in step of 5)
 DMxxx-P156-48BKS (xxx=165 to 210 in step of 5)
 DMxxx-P156-48LS (xxx=165 to 230 in step of 5)
 DMxxx-P156-48BLS (xxx=165 to 210 in step of 5)
 DMxxx-P156-36S (xxx=125 to 175 in step of 5)
 DMxxx-P156-36BKS (xxx=125 to 155 in step of 5)
 DMxxx-P156-24S (xxx=85 to 115 in step of 5)
 DMxxx-P156-24BKS (xxx=85 to 105 in step of 5)
 xxx is standing for rated output power at STC

Parameters:

Rated Output Power at STC:	See attachment
Fire Safety Class:	Class C
Application Class:	Class A
Max. System Voltage:	1000V DC
Test Laboratory:	Yangzhou Opto-electrical products testing institute. No.10 West Kaifa Road, Yangzhou, 225009 Jiangsu, P.R.China.
Construction:	Framed, with Junction box, cable and connector.

Tested according to:

EN 61730-2:2007/A1:2012
 EN 61730-1:2007/A2:2013

Page 2 of 4