



DMEGC Quality.Performance. Value.

MONO CRYSTALLINE MODULE


OPJ300-LV SMART SERIES

DM290-M156-60BS

60 x 6" /280 - 290W

Wattages:

280 / 285 / 290



SolarEdge power optimizer OPJ300-LV
Module embedded solution



Safer Installations

Unique Pass-Thru connector for easy module pashing and yield replacement



Power-Positive Tolerance

Guaranteed power output (0/+3%)



Up to 25% higher energy yield

Per-module Maximum Power Point Tracking (MPPT)

Mitigates all types of modules mismatch-loss, from manufacturing tolerance to partial shading



High module conversion efficiency

Module efficiency up to 17.72% achieved through advanced cell technology and manufacturing capabilities

www.dmegcsolar.com

Superior Manufacturing-Quality Assurance




- All modules are manufactured using TQC & SPC quality control systems
- Advanced cell sorting to avoid electric mismatch
- 100% EL Test-before lamination & prior to shipment
- Comprehensive Safety and Reliability tests are performed

OPJ300-LV Module Embedded Solution




DMEGC Smart Module comes with SolarEdges Power Optimizer platform which enables a number of smart functions

Warranty



- 10 Years Manufacturers Warranty
- 10 Years Warranty, 90% power output
- 25 Years Warranty, 80% power output

Visible Quality



- Durable, high-quality
- Rigid construction: 5400Pa & 2400Pa rated assembly




Electrical Specifications

* STC irradiance of 1000W/m² spectrum AM 1.5 and cell temperature of 25°C

Module Type	Pm(W)	Tolerance	Imp(A)	Vmp(V)	Isc(A)	Voc (V)	Module Efficiency
DM280-M156-60BS	280	0/+3%	8.87	31.60	9.32	38.89	17.11%
DM285-M156-60BS	285	0/+3%	8.94	31.90	9.39	39.10	17.41%
DM290-M156-60BS	290	0/+3%	9.02	32.20	9.46	39.31	17.72%

Mechanical Data

Cell Type	DMTD5B157-210
Cell Arrangement	60(6x10)
Module Structure	Glass/ EVA / Backsheet(white)
Glass Thickness	3.2mm
Application Class	Class A at IEC 61730
Junction Box Rating	IP 67
Cables	1000mm/4mm ²
Connector Type	MC4
Fire Rating Class	Class C



(Back side)
Note:mm[inch]

Maximum Ratings

Operating Temperature	-40°C to +85°C
Maximum Load Capacity	Snow 5400Pa / Wind 2400Pa
Maximum System Voltage	600V DC(UL) / 1000V DC(IEC)
Maximum Series Fuse Rating	15A
Number of Diodes	3

Packaging


* frame sizes (35mm/40mm) available upon request

Module Dimensions	1650x992x40mm	1650x992x35mm
Weight	19kg	18.2kg
Pallet Dimensions	1700x1130x1130	1700x1130x1130
Container	40' HQ	40' HQ
Pieces per Pallet	26	29
Pallets per Container	28	28
Pieces per Container	728	812
Gross Weight per Pallet	535kg	570kg
Gross Weight per Container	14,980kg	15,960kg


Temperature Characteristics

Nominal Operating Cell Temperature (NOCT)	45°C±2°C
Temperature Coefficient of Isc	+0.043%/°C
Temperature Coefficient of Voc	-0.320%/°C
Temperature Coefficient of Pmax	-0.420%/°C

Current-Voltage&Power-Voltage Curve(290W)



Temperature Dependence of Isc, Voc, Pmax



Hengdian Group DMEGC Magnetics Co., Ltd.
Hengdian Industrial Zone, Dongyang City
Zhejiang Province, China 322118

Tel: 0086-579-8658-8825 Fax: 0086-579-8655-4845
Email: solar@dmegc.com.cn
www.chinadmegc.com www.dmegcsolar.com