



Product Service

CERTIFICATE

No. Z2 076043 0090 Rev. 02

Model(s):

DMHxxxM6A-144SW, (xxx=380-395, in steps of 5)
 DMHxxxM6A-144BW, (xxx=380-395, in steps of 5)
 DMxxxG1-72HSW, (xxx=380-395, in steps of 5)
 DMxxxG1-72HBW, (xxx=380-395, in steps of 5)
 DMHxxxM6A-120SW, (xxx=320-325, in steps of 5)
 DMHxxxM6A-120BW, (xxx=320-325, in steps of 5)
 DMxxxG1-60HSW, (xxx=320-325, in steps of 5)
 DMxxxG1-60HBW, (xxx=320-325, in steps of 5)
 xxx is standing for the rated output power at STC

Parameters:

Construction:	Framed, with Junction box, Cable and Connectors.
Safety Class :	Class II
Maximum System Voltage:	1500 V DC
Fire Safety Class:	Class C according to UL 790
PID Test Condition:	-1500 V DC, 85 °C, 85 % RH, 96hours
PID testing method is according to IEC TS 62804-1:2015.	

Tested according to:

IEC 61215-1:2016
 IEC 61215-1-1:2016
 IEC 61215-2:2016
 IEC 61730-1:2016
 IEC 61730-2:2016
 PPP 58042B:2015

Production Facility(ies):

076053